

## Y 系列(IP23)

### 主要规格及技术参数

型号	功率 (kW)	转速 (r/min)	电流 (A)	效率 (%)	功率 因数	堵转电 流倍数	堵转转 矩倍数	最大转 矩倍数	振动 (mm/s)	噪声 dB (A)
Y200M-2	45	2940	84	91	0.89	7.0	1.9	2.2	2.8	90
Y200L-2	55		103	91.5						
Y225M-2	75	2955	140							
Y250S-2	90	2965	167	92	0.90	6.8	1.8	2.0	4.5	105
Y250M-2	110		201	92.5			1.7			
Y280M-2	132		241				1.6			
Y315S-2	160		292				1.4			
Y315M1-2	185		338							
Y315M2-2	200		363	93	0.88	6.5	1.0	107		
Y315M3-2	220		397	93.5						
Y315M4-2	250		460	93.8						
Y355M2-2	280	2970	514	94.0	0.89	6.5	1.0	107		
Y355M3-2	315		572	94.3						
Y355L1-2	355		643	94.3						
Y200M-4	37	1465	71	90.5	0.87	7.0	2	2.8	87	
Y200L-4	45		86	91.5						
Y225M-4	55	1475	104		0.88	6.8	2.2	4.5	103	
Y250S-4	75	141	92	1.8						
Y250M-4	90	168	92.5	2.0						
Y280S-4	110	205		1.7						
Y280M-4	132	245	93	1.8						
Y315S-4	160	297		1.4						
Y315M1-4	185	342	93.5			0.89	6.5	1.8	106	
Y315M2-4	200	368	93.8							
Y315M3-4	220	404	94.0	0.90	6.5	2.0	4.5	100		
Y315M4-4	250	458	94.3							
Y355M2-4	280	507		94.3	0.87	6.5	1.7	2.8	81	
Y355M3-4	315	564	94.5							
Y355L1-4	355	634	94.5							
Y200M-6	22	970	44	89	0.85	6.5	1.7	2.8	84	
Y200L-6	30		60	89.5						
Y225M-6	37	980	71	90.5	0.87	6.5	1.8	4.5	87	
Y250S-6	45		87	91	0.86					
Y250M-6	55		106		0.87					
Y280S-6	75	985	143	91.5	0.88	6.5	1.3	1.8	4.5	100
Y280M-6	90		169	92						
Y315S-6	110		207	93.0	0.87					
Y315M1-6	132		247	93.5						
Y315M2-6	160	298	93.8							

型号	功率 (kW)	转速 (r/min)	电流 (A)	效率 (%)	功率 因数	堵转电 流倍数	堵转转 矩倍数	最大转 矩倍数	振动 (mm/s)	噪声 Db (A)						
Y355M1-6	185	985	344	94.0	0.87	6.0	1.1	1.8	4.5	100						
Y355M2-6	200		372													
Y355M3-6	220		404													
Y355M4-6	250		458	94.3	0.88											
Y355L1-6	280		513	94.3												
Y200M-8	18.5	730	41	88.5	0.78		1.7	2.0	2.8	81						
Y200L-8	22		48	89	0.78		1.8									
Y225M-8	30	735	63	89.5	0.81		1.7				4.5	84				
Y250S-8	37		78	90	0.80		1.6									
Y250M-8	45		94	90.5			1.8									
Y280S-8	55		115	91			0.81	1.3								
Y280M-8	75		154	91.5												
Y315S-8	90	740	183	92.2	0.81		1.1	1.8	4.5	93						
Y315M1-8	110		222	92.8												
Y315M2-8	132		265	93.3												
Y355M2-8	160		321	93.5												
Y355M3-8	185		371	93.5												
Y355M4-8	200		401													
Y355L1-8	220		439	94.0												
Y355L2-8	250		512	0.79												
Y315S-10	55		590	123		91.5					0.74	5.5	1.2	1.8	4.5	93
Y315M1-10	75			165		92.0					0.75					
Y315M2-10	90	196		0.76												
Y355M2-10	110	232		92.5	0.78											
Y355M3-10	132	274		92.8	0.79											
Y355L1-10	160	332														
Y355L2-10	185	383		93.0												
Y355M4-12	90	530		201	92.0	0.74	1.0	1.8	4.5	93						
Y355L1-12	110			241	92.3	0.75										
Y355L2-12	132			289	92.5											

## 安装型式及尺寸

机座号	级数	尺寸 (mm)																
		A	B	C	D	E	FxGD	G	H	K	AB	AC	AD	AA	BB	HA	HD	L
200M	2、4	318	267	133	60	140	18x11	53	200	19	400	465	350	80	350	26	570	820
200L	6、8		305												393			886
Y225M	2	356	311	149	65	140	18x11	58	225	19	450	520	395	87	395	28	640	880
	4、6、8																	
Y250S	2	406	311	168	75	140	20x12	67.5	250	24	510	550	410	100	415	32	600	930
	4、6、8																	
Y250M	2	406	349	168	65	140	18x11	58	250	24	510	550	410	100	455	32	600	960
	4、6、8																	
Y280S	4、6、8	457	368	190	80	170	22x14	71	280	24	570	610	485	110	530	35	655	1090
Y280M	2		419		65	140	18x11	58										80
	4、6、8	419	80	170	22x14	71	581	1140										
Y315S	2	508	406	216	70	140	20x12	62.5	315	28	640	792	586	115	690	48	760	1130
	4-10				90	170	25x14	81							640	45		1160
Y315M	2	508	457	216	70	140	20x12	62.5	315	28	640	792	586	115	690	48	760	1240
	4-10				90	170	25x14	81							640	45		1270
Y355M	2	610	560	254	75	140	20x12	67.5	355	28	733	980	630	170	880	51	1120	1550
	4-10				100	210	28x16	90										1620
Y355L	2	610	630	254	75	140	20x12	67.5	355	28	733	980	630	170	880	51	1120	1620
	4-10				100	210	28x16	90										1690

